

PART NO.	UPC	DESCRIPTION	FINISH	QTY	LBS
Compression x Slip-Joint - Straight					
03345X C	026613137940	1/2" Nom Comp x 7/16" & 1/2" Slip-Joint	Chrome	60	17.6
03345X C1	026613136028	1/2" Nom Comp x 7/16" & 1/2" Slip-Joint	Chrome	20	6.1



Compression x Flare - Angle					
0FCR19X C	026613150499	1/2" Nom Comp x 3/8" OD Flare	Chrome	60	14.2



FIP x Compression - Angle					
OR07X C	026613136844	1/2" FIP x 1/4" OD Comp	Chrome	60	14.3
OR07X C1	026613135939	1/2" FIP x 1/4" OD Comp	Chrome	20	5.0
OR15X C	026613137575	3/8" FIP x 3/8" OD Comp	Chrome	60	11.3
OR15X C1	026613135908	3/8" FIP x 3/8" OD Comp	Chrome	20	4.0
OR15X R	026613153476	3/8" FIP x 3/8" OD Comp	Rough	60	12.6
OR35X C	026613150772	3/8" FIP x 1/2" OD Comp	Chrome	60	13.4
OR17X C	026613138176	1/2" FIP x 3/8" OD Comp	Chrome	60	14.4
OR17X C1	026613135793	1/2" FIP x 3/8" OD Comp	Chrome	20	5.0
OR17X R	026613138565	1/2" FIP x 3/8" OD Comp	Rough	60	15.7
OR17X R1	026613138152	1/2" FIP x 3/8" OD Comp	Rough	20	5.5
OR27X C	026613150734	1/2" FIP x 7/16" OD Comp	Chrome	60	14.3
OR37X C	026613138596	1/2" FIP x 1/2" OD Comp	Chrome	60	16.2
OR37X C1	026613135748	1/2" FIP x 1/2" OD Comp	Chrome	20	5.6
OR37X R	026613153520	1/2" FIP x 1/2" OD Comp	Rough	60	17.5



FIP x Compression - Straight					
OR10X C	026613154275	3/8" FIP x 3/8" OD Comp	Chrome	60	14.1



Variations

See page 112 for Available Variations



Lock Shield
Loose Key
Add Prefix "S"



Lock Shield
Screwdriver Slot
Add Prefix "SS"



Stuffing Box
Add Prefix "T"



Sweat and loose key stops are furnished with brass stems. All others are furnished with corrosion resistant P.O.M. stems. Brass Stem (Non-Sweat) Add Suffix "Z" e.g., OCR19Z C



Stuffing Box
Lock Shield
Loose Key
Add Prefix "ST"



Stuffing Box
Lock Shield
Screwdriver Slot
Add Prefix "SST"



Cross Handle
Add Prefix "X"



Round (Brass) Handle
Add Prefix "XX"

■ Denotes best selling Multi-Turn Supply Stops.