

Retrofit Roof Drain

SPECIFICATION:

Product should be item code checked below as manufactured by IPS Corporation.

- Constructed of a heavy gauge (.081) spun aluminum
- Quick and easy to install and maintain
- Bolt-in-place strainer dome
- Efficient and economical



• Flange size: 16 1/2" (419 mm)

Strainer Diameter: 7 1/2" (191 mm)/ height: 5" (127 mm)

• Overall length of drain outlet: 12" (305 mm)



Installation:

Determine exact dimension of drain pipe. Select appropriate drain size to fit the existing drain pipe. Retro-fit drain may be set in a shallow bowl or directly on roof membrane with deck opening of at least 1" (25 mm) grater than the leader size into which the drain will be inserted. The flange is adaptable to all membranes.

Remove the exterior restraining tape and immediately set the retro drain in place. The released tape gradually expands to fill the space between the drain and the existing drain sleeve making the connection watertight.

Qty	Product Code	Drain Pipe Size	Units/Case	Lbs./Case	Outlet Outside Diameter	Outlet Length
	86111	3" (76 mm)	6	30	2.75" (70 mm)	0.727
	86112	4" (102 mm)	6	30	3.75" (95 mm)	0.727
	86113	6" (152 mm)	6	30	5.75" (146 mm)	0.727

